

AR15.COM

TACTICAL SLING

A GUIDE FROM GLLGLL



CONTENTS

- **MATERIALS**
- **ASSEMBLY**
- **VARIATION**
- **USAGE**

MATERIALS

- 7 ½ ft. nylon web, 1.5" wide
- 5 or 7 in. nylon web, 1.5" wide
- Two 15 in. nylon web, 1" wide
- Two buckles, 1.5" wide
- Three slide locks, 1.5" wide
- Two slide locks, 1" wide
- Tape measure
- Scissors
- Lighter for sealing the nylon web



ASSEMBLY

1. Slide a female buckle end onto the 1.5" web and then put a slide lock on the tail of the web itself. Note the direction of the slide and female end.



2. Loop the web back and through the slide lock installed in Step 1. Make your loop 27" long. Note the direction of the slide and female end.

3. Slide a 1.5" slide lock on to the web, leaving the open end pointing out. This will now be the outside of the sling.



ASSEMBLY, CONTINUED



4. Assemble this piece using the 5 or 7" piece of 1.5" wide web and the female and male ends of 1.5" buckles. Pay close attention to the web's routing and the direction of the buckles. If desired, cut down the webbing after the threading process.

5. Slide the assembly from Step 4 onto the open end of the sling.



6. Thread the last male buckle and slide stop on the open end of the sling. Note that the tail of the web is on the outside of the sling, as described in Step 3.

7. Tighten Step 6, leaving $\frac{1}{4}$ - $\frac{1}{2}$ " of webbing past the slide lock.



8. Slide the 1" slide locks onto the 1" webbing. Slide one assembly onto the open end of the 1.5" lock from Step 3. Slide the other through the

outside of the male buckle from Steps 7-8.

9. Tighten all webbing and snap all the buckles.



VARIATION

T-Strap Rear Mount: Sew an additional length of 1 or 1.5" webbing onto the rear sling mount. Loop the rear sling mount around the stock to determine the desired webbing length.



USAGE

Front Carry: Note how the sling loops over the left shoulder and under the right arm.



Right-Side Carry: This position works well for most applications. Sliding the gun further back will sling the firearm behind the back.

USAGE, CONTINUED

Left-Side Carry: This position is excellent for transition drills. Dropping the gun will naturally slide it to this position, clearing the way for holster use on the right thigh or hip.



Backpack Carry: By splitting the sling straps for each shoulder, the weapon can be carried like a backpack for comfortable long-term carry.

Ready Position: Present the weapon from the left side carry position. Dropping the gun will naturally return it to its prior location.



Shoulder Transition: Uncouple the forward-most buckle. This adds a foot or so to the sling length, making it possible to shoot left handed while slung for a right-handed shooter. Reverse the position for left-handed shooters.